product data sheet

item no. G5.800.0023.7

distributor MST20I5V 3P1 25 GEC7

METALYNX² degree of protection (ip) IP20, number of inputs 1, number of outputs 3, color of coding/ contact carrier yellow, ral number coding/contact insert 1032, halogen free yes, housing material polyamide, fire load 1.611 kWh/St, contact material CuZn, surface finish silver-plated, pollution degree 2, rated impulse voltage 4 kV, length 162 mm, height 38.4 mm, width 150.6 mm

item no.	G5.800.0023.7
EAN	4049088247033
order unit	16 piece(s)

certificates / approvals

technical data

general

rated impulse voltage	4 kV
pollution degree	2
lockable	self-locking (unlocking by tool)
color of coding/ contact carrier	yellow
RAL number coding/contact insert	1032

lead

model	H-distributor
microfuse (6,3x25 mm)	
drop	
no. of poles on drop	
cross section of drop	
termination of drop	
length of drop	
lenght of open end	
stripping length of drop	
design of conductor ends	
color of the coding pin	yellow (C7)
wiring system	
internal cross secction	2.5 mm²

model

number of inputs	1
number of outputs	3
type of fastening	yes
degree of protection (IP)	IP20
type of distributor	H-Distributor with switching functionality

material

housing material	polyamide
halogen free	yes
contact material	CuZn
fire load	1.611 kWh/St
insulation components continous temperature	100 °C
surface finish	silver-plated

dimensions

length	162 mm
width	150.6 mm
height	38.4 mm